ISUZU D-MAX 1.9 Ddi DOUBLE CAB 4X4 LS A/T

ENGINE	
Displacement (cc)	1 898
No. of Cylinders	4
No. of Valves	16
Power (kW) @ r/min	110 @ 3 600
Torque (Nm) @ r/min	350 @ 1 800 - 2 600
800 mm Water Depth Protection	Standard
Intercooler	Standard
FUEL CONSUMPTION	
Combined Cycle (Litres/100 km)	-
Combined CO ₂ Emissions (g/km)	-
TRANSMISSION	
Transmission Type	6-Speed Automatic
4WD Selector	Standard
Low Range Ratio	2.482
FRONT DIFFERENTIAL	-
Shift on the Fly up to 100 km / hour	Standard
REAR DIFFERENTIAL	
Differential Lock	-
CHASSIS DESIGN	•
Front Wheel Suspension	Coil Over Shock
· · · · · · · · · · · · · · · · · · ·	Leaf Spring
Rear Wheel Suspension	Overslung
Shock Absorbers	Twintube
	Gas Pressurised
Suspension	High-Ride
Skid Plate Guard Front and Rear	Standard
Engine Sump Guard Transfer Case Guard	– Standard
Oil Pan Guard	Standard
	Stanudiu
WHEELS & TYRES	
Tyre Size	255 / 65 R 17 AT
Tyre Size Wheels Size / Type	17" X 7.0J-33 Alloy
Tyre Size Wheels Size / Type Spare Wheel Size / Type	
Tyre Size Wheels Size / Type Spare Wheel Size / Type	17" X 7.0J-33 Alloy
Tyre Size Wheels Size / Type Spare Wheel Size / Type	17" X 7.0J-33 Alloy
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS	17" X 7.0J-33 Alloy
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel –
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265 1 870
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265 1 870 1 805
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265 1 870 1 805 3 125
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Height (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 227
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 227 1 495
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 227 1 495 1 530
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm) Loadbox Width (mm)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 227 1 495 1 530 490
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm) Loadbox Width (mm) Loadbox Width (mm)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 227 1 495 1 530 490 30
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm) Loadbox Width (mm) Loadbox Depth (mm) Approach Angle (°)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 227 1 495 1 530 490 30 24
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm) Loadbox Length (mm) Loadbox Depth (mm) Loadbox Depth (mm) Approach Angle (°) Departure Angle (°)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 227 1 495 1 530 490 30 24 22.5
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm) Loadbox Length (mm) Loadbox Depth (mm) Approach Angle (°) Departure Angle (°)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 227 1 495 1 530 490 30 24
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm) Loadbox Length (mm) Loadbox Depth (mm) Loadbox Depth (mm) Approach Angle (°) Departure Angle (°) Breakover Angle (°)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 227 1 495 1 530 490 30 24 22.5
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm) Loadbox Length (mm) Loadbox Vidth (mm) Loadbox Depth (mm) Approach Angle (°) Departure Angle (°) Breakover Angle (°) Breakover Angle (°) Wading Depth (mm)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 227 1 495 1 530 490 30 24 22.5
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm) Loadbox Length (mm) Loadbox Depth (mm) Approach Angle (°) Departure Angle (°) Breakover Angle (°) Breakover Angle (°) Wading Depth (mm) MASS / CAPACITY Gross Axle Mass – Front (GA1) (kg)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 2 27 1 495 1 530 490 30 2 24 2 2.5 800
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm) Loadbox Length (mm) Loadbox Depth (mm) Approach Angle (°) Departure Angle (°) Breakover Angle (°) Breakover Angle (°) Wading Depth (mm) MASS / CAPACITY Gross Axle Mass – Front (GA1) (kg) Gross Axle Mass – Rear (GA2) (kg)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 227 1 495 1 530 490 30 24 22.5 800 1 450
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm) Loadbox Length (mm) Loadbox Depth (mm) Approach Angle (°) Departure Angle (°) Breakover Angle (°) Breakover Angle (°) Wading Depth (mm) MASS / CAPACITY Gross Axle Mass – Front (GA1) (kg) Gross Vehicle Mass (GVM) (kg)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 227 1 495 1 530 490 30 24 22.5 800 1 450 1 450 1 910
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm) Loadbox Length (mm) Loadbox Depth (mm) Approach Angle (°) Departure Angle (°) Breakover Angle (°) Breakover Angle (°) Wading Depth (mm) MASS / CAPACITY Gross Axle Mass – Front (GA1) (kg) Gross Axle Mass – Rear (GA2) (kg) Gross Vehicle Mass (GCM) (kg)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - - - - - - - - - - - - - - - - - -
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm) Loadbox Length (mm) Loadbox Width (mm) Loadbox Depth (mm) Approach Angle (°) Departure Angle (°) Breakover Angle (°) Breakover Angle (°) Wading Depth (mm) MASS / CAPACITY Gross Axle Mass – Front (GA1) (kg) Gross Vehicle Mass (GVM) (kg) Gross Combined Mass (GCM) (kg) Tare Mass (kg)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - - - - - - - - - - - - - - - - - -
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm) Loadbox Length (mm) Loadbox Depth (mm) Approach Angle (°) Departure Angle (°) Breakover Angle (°) Breakover Angle (°) Breakover Angle (°) Gross Axle Mass – Front (GA1) (kg) Gross Axle Mass – Rear (GA2) (kg) Gross Combined Mass (GCM) (kg) Tare Mass (kg) Payload (kg)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 227 1 495 1 530 490 30 24 22.5 800 - 1 450 1 910 3 100 5 000 1 935 ^{#1}
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm) Loadbox Length (mm) Loadbox Length (mm) Approach Angle (°) Departure Angle (°) Breakover Angle (°) Breakover Angle (°) Wading Depth (mm) MASS / CAPACITY Gross Axle Mass – Front (GA1) (kg) Gross Vehicle Mass (GVM) (kg) Gross Combined Mass (GCM) (kg) Tare Mass (kg) Payload (kg) Towing Capacity (kg): Unbraked Trailer	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 227 1 495 1 530 490 30 24 22.5 800 - 1 450 1 910 3 100 5 000 1 935 ^{#1}
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm) Loadbox Length (mm) Loadbox Depth (mm) Approach Angle (°) Departure Angle (°) Breakover Angle (°) Breakover Angle (°) Breakover Angle (°) Gross Axle Mass – Front (GA1) (kg) Gross Axle Mass – Rear (GA2) (kg) Gross Combined Mass (GCM) (kg) Tare Mass (kg) Payload (kg)	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 227 1 495 1 530 490 30 24 22.5 800 - 1 450 1 910 3 100 5 000 1 935 ^{#1}
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm) Loadbox Length (mm) Loadbox Width (mm) Loadbox Width (mm) Loadbox Depth (mm) Approach Angle (°) Departure Angle (°) Breakover Angle (°) Breakover Angle (°) Breakover Angle (°) Breakover Angle (°) Gross Axle Mass – Front (GA1) (kg) Gross Axle Mass – Rear (GA2) (kg) Gross Combined Mass (GCM) (kg) Tare Mass (kg) Payload (kg) Towing Capacity (kg): Unbraked Trailer	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 227 1 495 1 530 490 30 24 22.5 800 1 450 1 910 3 100 5 000 1 935 ^{#1}
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm) Loadbox Length (mm) Loadbox Depth (mm) Approach Angle (°) Departure Angle (°) Breakover Angle (°) Breakover Angle (°) Breakover Angle (°) Gross Axle Mass – Front (GA1) (kg) Gross Axle Mass – Rear (GA2) (kg) Gross Axle Mass – Rear (GA2) (kg) Gross Combined Mass (GCM) (kg) Tare Mass (kg) Payload (kg) Towing Capacity (kg): Unbraked Trailer Towing Capacity / Rating (kg): Braked Trailer	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 227 1 495 1 530 490 30 24 22.5 800 1 450 1 910 3 100 5 000 1 935 ^{s1} 1 105 ^{s1} - -
Tyre Size Wheels Size / Type Spare Wheel Size / Type Tyre-Pressure Monitoring Sensor DIMENSIONS Length (mm) Width (mm) Height (mm) Wheelbase (mm) Front / Rear Track (mm) Rear Overhang (mm) Ground Clearance (mm) Loadbox Length (mm) Loadbox Length (mm) Loadbox Vidth (mm) Loadbox Depth (mm) Approach Angle (°) Departure Angle (°) Breakover Angle (°) Breakover Angle (°) Breakover Angle (°) Bross Axle Mass – Front (GA1) (kg) Gross Axle Mass – Rear (GA2) (kg) Gross Combined Mass (GCM) (kg) Tare Mass (kg) Payload (kg) Towing Capacity / Rating (kg): Braked Trailer	17" X 7.0J-33 Alloy 17" X 7.0J-33 Steel - 5 265 1 870 1 805 3 125 1 570 / 1 570 1 250 227 1 495 1 530 490 30 24 22.5 800 1 450 1 910 3 100 5 000 1 935 ^{s1} 1 105 ^{s1} - -

SAFETY FEATURES	
Anti-Lock Braking System (ABS)	Standard
Electronic Brake-Force Distribution (EBD)	Standard
Brake-Assist System (BAS)	Standard
Electronic Stability Control (ESC) with Traction Control	Standard
Hill-Start Assist (HSA)	Standard
Hill-Descent Control (HDC)	Standard
Trailer Sway Control	Standard
Brake-Override Accelerator (BOA)	Standard
Cruise Control	Standard
Seatbelt Reminder	Driver and Passenger
Occupant Detection Sensor	Passenger
Driver and Passenger Airbags	Standard
Front Seat Side Airbags	Standard
Curtain Airbags	Standard
Knee Airbag	Driver Standard
Side-Impact Protection Bars Speed-Sensitive Door Lock	Standard
	Standard with
ISOFIX Child-Seat Attachment Parking Distance Sensors	Top Tether Rear
Rear-View Camera	Standard
Emergency Stop Signal	Standard
Blind-Spot Monitor	-
Rear Cross-Traffic Alert	-
Rear Radar	_
SECURITY FEATURES	
Remote-Controlled Central Locking	Standard
Remote Keyless Entry	Standard
Passive Entry Start System (PESS)	-
Child-Proof Rear Door Locks	Standard
Anti-Theft Alarm System	Standard
Ultrasonic Alarm	Standard
Transponder Immobiliser System	Standard
Selectable Door Unlock	Standard
Walk-Away Auto Door Look	-
INTERIOR / EXTERIOR LIGHTING	3
Front Reading Lamps	Standard
Interior Courtesy Lamp	Standard
Illuminated Entry	Standard
Front Fog Lamps	Standard
Daytime Running Lights (DRL)	Halogen
Headlamps	Halogen
Headlamp Levelling	Manual
Headlamps 'ON' Warning Buzzer	Standard
Automatic On/Off Headlamp	-
Turn Indicator Lamp on Door	-
Rear Tail Lamps, Combination	Bulb
High-Mounted Centre Stop Lamp	Standard
Follow-Me-Home Headlamps	Standard
EXTERIOR FEATURES	
Towbar	Optional (2.1T)
Exterior Mirror	Body Colour, Power Adjustment and Manual Folding,
Roof Rails	Side Indicator
Sports Bar	
Side-Steps	- Standard Black
· · · · · · · · · · · · · · · · · · ·	adi a Diuch
Mudflaps	Front and Rear

Hydraulic
Manual
Standard
Standard
Standard

Restraint

Power Socket – Auxiliary 12V IP Mounted	1
Cigarette Lighter without Illumination	Standard
Lockable Glove Box	Standard
Utility Box on Glove Box	Standard, High Type
Steering Column Adjustment	Tilt and Telescopic
Steering Wheel Trim	Leather
Steering Wheel Multi-Functional Controls	Audio and Auto Cruise
Front Seat Configuration	Bucket Seats (x2)
Rear Seat Configuration	60:40-Split Bench Cushion
Seat Trim	Cloth
Seat Adjustment	6-Way Manual Driver
Storage Pockets behind Front Seats	Standard
A-Pillar Assist Grip, Driver and Passenger	Standard
Roof-Mounted Assist Grips	Driver and Passengers
Floor Trim	Carpet with Heel Pad and Tibia Pad
Floor Tunnel Console with Integrated Cupholder	Standard
Centre Console Storage Box with Lid	Standard
Rear Heater Duct	Standard
Rear Ventilation Duct	-
Storage Box	-
Window Operation	Power Front and Rear with Driver One-Touch, Jam Protection
Rear Window	Fixed with Defogger

INFOTAINMENT	
Audio System	AM/FM Radio, 7" Touchscreen, Bluetooth® – Audio Streaming, Apple CarPlay® and Android Auto, Wi-Fi and Hands-Free Phone
USB Port (Music Playback and Device Link)	Standard
USB Charge Port	Rear
Speakers	8
Antenna	Standard

OPTIONS	
17" Alloy Wheel	-
18" Alloy Wheel and 265 / 60 R 18 Tyre (All Terrain)	Available
18" Alloy Wheel and 265 / 60 R 18 Tyre (H/T Terrain)	-
Differential Lock	Available
Hubcap Steel Wheel	-
Hubcap Alloy Wheel	-
Spare Tyre Steel	-
Spare Tyre Alloy	Available
Sports Bar – Black	Available
Sports Bar – Chrome	Available
Rear Sliding Window	Available
Leather Seat with Manual Adjustment	Available

WARRANTY / SERVICE INTERVALS	
Warranty ^{#2}	3 Years / 100 000 km
Anti-Corrosion Warranty ^{#2}	3 Years / Unlimited km
Service Plan	-
Service Intervals	12 Months or 10 000 km / 15 000 km

*1 Tare Mass for RHD E2 SMODS only - KENYA TBD
 *1 Payload for RHD E2 SMODS only - KENYA TBD
 *2 Excludes KENYA

